

Wavelength	Diameter	N. A	NO	Working distance s (mm)	Lens length	Focal length	Gradient constant	Product code
630	1.0	0.46 (55°)	1.611	0.00	2.59	1.02	0.606	
830	1.0	0.46 (55°)	1.601	0.00	2.62	1.04	0.599	
1310	1.0	0.46 (55°)	1.594	0.00	2.63	1.05	0.597	-10-25-1310-角度-镀膜
1550	1.0	0.46 (55°)	1.591	0.00	2.64	1.05	0.596	-10-25-1550-角度-镀膜
630	1.8	0.46 (55°)	1.611	0.00	4.63	1.83	0.339	
830	1.8	0.46 (55°)	1.601	0.00	4.73	1.88	0.332	
1310	1.8	0.46 (55°)	1.594	0.00	4.80	1.92	0.327	-18-25-1310-角度-镀膜
1550	1.8	0.46 (55°)	1.591	0.00	4.82	1.93	0.326	-18-25-1550-角度-镀膜
630	3.0	0.46 (55°)	1.611	0.00	7.63	3.01	0.206	
830	3.0	0.46 (55°)	1.601	0.00	7.78	3.09	0.202	
1310	3.0	0.46 (55°)	1.594	0.00	7.89	3.15	0.199	-30-25-1310-角度-镀膜
1550	3.0	0.46 (55°)	1.591	0.00	7.93	3.17	0.198	-30-25-1550-角度-镀膜
630	1.8	0.60 (74°)	1.658	0.00	3.76	1.44	0.418	
830	1.8	0.60 (74°)	1.646	0.00	3.82	1.48	0.411	
1310	1.8	0.60 (74°)	1.638	0.00	3.87	1.51	0.406	-18-25-1310-角度-镀膜
1550	1.8	0.60 (74°)	1.634	0.00	3.88	1.51	0.405	-18-25-1550-角度-镀膜

Wavelength	Diameter	N. A	NO	Working distance (mm)	Lens length	Focal length	Gradient constant	Product code
630	1.0	0.46 (55°)	1.611	0.13	2.38	1.03	0.606	
830	1.0	0.46 (55°)	1.601	0.13	2.41	1.05	0.599	
1310	1.0	0.46 (55°)	1.594	0.13	2.42	1.06	0.597	-10-25-1310-角度-镀膜
1550	1.0	0.46 (55°)	1.591	0.13	2.42	1.06	0.596	-10-25-1550-角度-镀膜
630	1.8	0.46 (55°)	1.611	0.23	4.26	1.85	0.339	
830	1.8	0.46 (55°)	1.601	0.24	4.35	1.90	0.332	
1310	1.8	0.46 (55°)	1.594	0.24	4.42	1.93	0.327	-18-25-1310-角度-镀膜
1550	1.8	0.46 (55°)	1.591	0.24	4.43	1.94	0.326	-18-25-1550-角度-镀膜
630	3.0	0.46 (55°)	1.611	0.38	7.02	3.04	0.206	
830	3.0	0.46 (55°)	1.601	0.39	7.15	3.12	0.202	
1310	3.0	0.46 (55°)	1.594	0.40	7.26	3.18	0.199	-30-25-1310-角度-镀膜
1550	3.0	0.46 (55°)	1.591	0.40	7.30	3.19	0.198	-30-25-1550-角度-镀膜
630	1.8	0.60 (74°)	1.658	0.18	3.46	1.45	0.418	
830	1.8	0.60 (74°)	1.646	0.18	3.52	1.49	0.411	
1310	1.8	0.60 (74°)	1.638	0.19	3.56	1.52	0.406	-18-25-1310-角度-镀膜
1550	1.8	0.60 (74°)	1.634	0.19	3.57	1.52	0.405	-18-25-1550-角度-镀膜

Wavelength	Diameter	N. A	NO	Working distances (mm)	Lens length	Focal length	Gradient constant	Product code
630	1.0	0.46 (55°)	1.611	0.26	2.18	1.06	0.606	
830	1.0	0.46 (55°)	1.601	0.27	2.20	1.08	0.599	
1310	1.0	0.46 (55°)	1.594	0.27	2.21	1.09	0.597	-10-25-1310-角度-镀膜
1550	1.0	0.46 (55°)	1.591	0.27	2.21	1.09	0.596	-10-25-1550-角度-镀膜
630	1.8	0.46 (55°)	1.611	0.47	3.89	1.89	0.339	
830	1.8	0.46 (55°)	1.601	0.48	3.97	1.94	0.332	
1310	1.8	0.46 (55°)	1.594	0.49	4.03	1.98	0.327	-18-25-1310-角度-镀膜
1550	1.8	0.46 (55°)	1.591	0.49	4.04	1.99	0.326	-18-25-1550-角度-镀膜
630	3.0	0.46 (55°)	1.611	0.78	6.40	3.11	0.206	
830	3.0	0.46 (55°)	1.601	0.80	6.53	3.19	0.202	
1310	3.0	0.46 (55°)	1.594	0.82	6.63	3.26	0.199	-30-25-1310-角度-镀膜
1550	3.0	0.46 (55°)	1.591	0.82	6.66	3.28	0.198	-30-25-1550-角度-镀膜
630	1.8	0.60 (74°)	1.658	0.37	3.15	1.49	0.418	
830	1.8	0.60 (74°)	1.646	0.38	3.21	1.53	0.411	
1310	1.8	0.60 (74°)	1.638	0.39	3.25	1.56	0.406	-18-25-1310-角度-镀膜
1550	1.8	0.60 (74°)	1.634	0.39	3.26	1.56	0.405	-18-25-1550-角度-镀膜